

Index

A

| | | | |
|----------------------|--|-------------------------|--|
| absorption | 2.1-6 , 4-8 , 6-9 , 6-25 | aqueous systems | 3.2-5 |
| absorption column | 6-22 | aromatics | 5-6 |
| acid | 3.1-2 | assurance | 1-2 |
| acid gas | 6-20 | azeotrope | 6-19 |
| activity coefficient | 6-2 , 6-23 | azeotropic distillation | 1-1 , 3.2-1 , 5-5 , 6-28 |
| alcohol | 6-5 | azeotropic mixtures | 1-3 , 5-2 , 5-4 , 6-19 |
| amine | 1-5 , 6-20 | | |

B

| | | | |
|--------------------|--|-------------------|--|
| batch | 6-31 | boundary crossing | 3.2-1 |
| batch distillation | 5-2 , 5-3 , 5-4 , 6-24 | bubble column | 6-3 , 6-4 , 6-11 |
| batch regime | 6-3 | bubbly flow | 6-11 |
| binary entrainer | 3.1-2 | | |

C

| | | | |
|------------------------|---|-------------------------------|--|
| CAMD | 1-1 | column | 2.1-4 , 4-4 , 4-7 , 5-1 , 6-30 |
| capacity | 2.1-3 , 2.2-7 | component efficiencies | 3.2-1 |
| carbon dioxide | 1-5 | computational fluid dynamics | PL2 , 6-10 |
| carbonic acid | 6-5 | computer aided solvent design | 1-1 |
| case-based reasoning | 3.1-6 | conceptual design | 3.2-2 |
| catalytic distillation | 3.4-3 , 4-4 | continuous distillation | 6-19 |
| catalytic packing | 4-5 , 6-29 | continuous regime | 6-3 |
| CFD | 2.2-3 , 2.2-5 , 2.2-6 , 6-8 , 6-11 , 6-12 , 6-13 | control | 3.4-3 |
| characteristic number | 2.1-2 | correlations | 6-12 |
| chemical | 5-5 , 6-4 | COSMO-RS | PL3 , 6-23 |
| clear liquid height | PL2 | crude oil | 3.3-1 |

D

| | | | |
|------------------------------|--|--------------------|--|
| Danckwert | 6-4 | dimethyl sulfoxide | 6-1 |
| decanter-distillation hybrid | 5-4 | dismutation | 4-1 |
| dehydration | 4-8 | DISQUAC | 6-1 |
| delayed boiling | 2.1-7 | distillation | PL1 , PL3 , PL4 , 1-1 , 2.1-1 , 2.1-6 , 2.2-2 , 3.1-3 , 3.1-4 , 3.2-4 , 3.2-5 , 3.3-5 , 3.4-1 , 5-7 , 6-9 , 6-12 , 6-14 , 6-16 , 6-21 , 6-27 , 6-31 |
| design | 3.1-3 , 6-30 | | |
| desulfurization | 6-25 | | |
| diffusion | 1-4 | | |

| | | | |
|-----------------------|--|------------------------|---|
| distillation boundary | 6-19 | distillation synthesis | 3.1-1 |
| distillation column | 3.3-4 , 3.4-2 , 6-18 | divided-wall columns | 3.4-1 , 5-6 |
| distillation control | 6-28 | driving force | 3.1-3 |
| distillation modeling | 6-23 | dualflow | 2.1-4 |
| distillation regions | 6-19 | dynamic behaviour | 6-18 |
| distillation surface | 3.2-1 | dynamic simulation | 3.4-2 |

E

| | | | |
|--------------------------------|---|----------------------------|--|
| effective area | 6-12 | equipment | PL4 |
| efficiency | 3.2-4 , 3.2-5 | ethanol dehydration | 6-28 |
| empirical model | 2.2-6 | excess enthalpy | 6-1 |
| energy integrated distillation | 3.3-2 | experimental investigation | 5-2 |
| energy efficiency | 3.3-1 | experimental validation | 6-24 |
| energy integration | 3.3-3 | experimental verification | 3.3-4 |
| entrainer | 1-3 , 5-5 | experiments | 4-5 |
| entrainment | 2.2-4 | extractive | 6-31 |
| equilibrium diagram | 6-25 | extractive distillation | PL3 , 1-1 , 1-3 , 3.2-2 , 5-2 , 5-6 |
| equilibrium stage | 3.2-1 , 4-7 | | |

F

| | | | |
|----------------------------|---|-----------------------|-----------------------|
| factorial design | 6-28 | flue gas | 6-25 |
| fatty acids esterification | 5-5 | foam fractionation | 5-1 |
| feasibility | 3.1-1 , 6-30 , 6-31 | formaldehyde | 6-26 |
| feasible separation region | 6-19 | fouling | 2.1-4 |
| feed inlet | 2.2-3 | froth density | PL2 |
| film thickness | 2.2-6 | froth height | PL2 |
| flood | 2.2-7 | full thermal coupling | 6-27 |
| flooding | 4-7 , 6-15 | future trends | 2.1-1 |
| flowsheet | 3.1-4 | | |

G

| | | | |
|---------------------|--|--------------------------------------|-----------------------|
| gas capacity | 6-17 | gas/vapour flow | 2.2-6 |
| gas flow rate | 6-4 | genetic algorithm | 5-3 |
| gas liquid flow | 6-10 | graphical conceptualising techniques | 3.1-2 |
| gas maldistribution | 2.2-5 , 6-14 | graphical tool | 6-30 |

H

| | | | |
|------------------------|-----------------------|---------------------------------------|---|
| hardware | 4-7 | heterogeneous azeotropic distillation | 3.1-2 , 3.2-3 , 5-4 , 6-28 |
| heat exchanger network | 3.3-1 | heterogeneous catalysis | 4-5 |
| heat integration | 3.3-1 | hexyl acetate | 4-5 |

| | | | |
|------------------|---|------------------------------|---|
| high performance | 2.1-2 | hydraulics of packed columns | 2.1-3 , 6-7 |
| highspeed tray | 6-6 | hydrodesulfurization | 4-6 |
| hybrid | 4-8 | hydrodynamics | 4-7 , 6-17 |
| hybrid column | 6-30 | hyperbranched polymers | PL3 , 1-3 |
| hybrid processes | 4-9 , 5-4 | | |

I

| | | | |
|-----------------------------------|-----------------------|------------------|--|
| ideal mixtures | 6-16 | interfacial area | 6-4 , 6-11 |
| inclined plate | 6-13 | internals | 4-4 |
| integrated process | 3.4-1 | ionic liquids | PL3 , 1-3 |
| integrated system | 3.1-3 | isopropylbenzene | 3.1-4 |
| integration of design and control | 3.3-2 | | |

L

| | | | |
|---------------------|-----------------------|---------------------|-----------------------|
| limestone | 6-25 | liquid distributors | 2.2-5 |
| liquid circulations | PL2 | liquid film flow | 2.2-6 |
| liquid collectors | 2.2-5 | loading | 6-15 |

M

| | | | |
|----------------------------|--|-------------------------------|--|
| maldistribution | 2.1-5 , 2.2-2 , 2.2-3 | minimum energy | 6-27 |
| malfunctions | PL1 | model | 3.1-3 |
| manifold | 3.1-1 | model predictive control | 3.4-1 |
| mass transfer | 1-5 , 4-7 , 6-7 , 6-20 | modeling | 3.2-5 , 3.4-3 , 4-4 , 4-5 , 6-24 , 6-25 |
| mass transfer coefficients | 6-3 | multicomponent | 1-4 , 3.1-1 , 6-16 |
| mass-transfer internals | 6-6 | multi-effect | 3.3-3 |
| mathematical modelling | 6-21 | multiplicity of steady states | 6-18 |
| Maxwell-Stefan equations | 1-4 , 3.2-1 , 4-7 | multivessel batch column | 5-4 |
| measurements | 6-2 | MVG tray | 6-8 |
| methyl acetate | 4-7 | | |
| middle vessel column | 5-2 | | |

N

| | | | |
|----------------------------|-----------------------|----------------------|---|
| network pinch | 3.3-1 | nonequilibrium stage | 3.2-1 , 3.2-3 , 4-7 |
| neural network | 6-22 | novel process | 5-1 |
| nitric acid | 6-22 | NTSM | 2.1-2 |
| non linear data regression | 1-2 | | |

O

| | | | |
|-------------------|---------------------|------------------|--|
| olefin isomer | 4-2 | optimal solution | 3.1-3 |
| optimal design | 5-3 | optimisation | 3.3-4 , 3.4-3 , 6-28 |
| optimal operation | 5-3 | oxygenate | 3.1-2 |

P

| | | | |
|----------------------------|---|----------------------|--|
| packed column | 2.1-5 , 2.2-2 , 2.2-3 , 2.2-5 , 6-21 | pinch point | 3.2-2 , 6-19 |
| packing | 2.1-4 , 2.1-5 , 2.1-6 , 6-9 | plate behaviour | 3.2-4 |
| parameter estimation | 6-2 | practical experience | PL1 |
| PC-SAFT | PL3 | prediction | 1-4 , 6-2 |
| performance | 2.1-1 , 2.2-1 | preheat train | 3.3-1 |
| pervaporation | 4-3 , 4-8 | pressure drop | 2.1-2 , 6-14 , 6-15 , 6-17 |
| petrochemical cuts | 5-6 | process design | 3.3-5 |
| phase equilibrium | 5-5 , 6-2 | process integration | 3.3-5 |
| photographic method | 6-4 | process operation | 3.3-5 |
| physical absorption | 6-3 | process simulation | 4-3 , 6-28 |
| physical methods | 6-4 | process synthesis | PL4 , 3.1-6 , 6-30 |
| physicochemical phenomena | 3.2-5 | product region | 3.1-1 |
| physicochemical properties | 3.2-5 | property integration | 3.1-5 |
| pinch | 3.1-4 | property prediction | PL3 |
| | | pump-arounds | 4-7 |

Q

| | | | |
|------------------------------------|-----------------------|--------------------|-----------------------|
| quality | 1-2 | quaternary systems | 3.1-2 |
| quaternary azeotropic distillation | 3.2-1 | | |

R

| | | | |
|-------------------------------------|---|-----------------------------|---|
| random | 6-9 | recycle structure | 3.1-1 |
| Raschig Super-Ring | 2.1-6 | recycle systems | 6-18 |
| RBF network | 6-22 | redistribution | 2.1-5 , 4-1 |
| reaction kinetics | 1-5 , 4-3 | relief | 3.4-2 |
| reactive distillation | PL4 , 4-1 , 4-3 , 4-5 , 4-6 , 4-7 , 6-5 , 6-7 , 6-29 | removal | 3.1-2 |
| reactive extractive distillation | 4-2 | residence time distribution | PL2 |
| reactive packing | 6-7 | retrofit | 3.3-1 |
| reactive separation | 4-4 , 5-5 | retrofit design | 3.3-1 |
| real mixtures | 6-16 | reversible distillation | 6-27 |
| recovery of olefins from oxygenates | 3.1-2 | Rivulet | 6-13 |
| rectification body method | 3.2-2 | Rombopak | 2.1-2 |
| recycle | 3.1-1 | rotating cone | 2.2-6 |

S

| | | | |
|----------------------------|--|--------------------------|---|
| safety | 3.4-2 | simulation | 3.2-3 , 3.2-4 , 3.2-5 , 4-4 , 4-5 , 6-10 , 6-21 , 6-22 , 6-24 |
| scale effects | PL2 | slurries | 5-7 |
| scale-up | 4-5 , 6-29 | SO ₂ | 6-25 |
| selective entrainers | 1-3 | solvent recovery | 4-9 |
| selective solvents | 1-3 | solvents | 1-1 |
| selectivity | 6-20 | spray scrubbing | 6-25 |
| self-optimizing control | 3.3-3 | startup | 3.3-4 |
| separation | 6-26 | steady state simulations | 3.1-2 |
| separation factor | 1-3 | stochastic optimisation | 5-3 |
| shortcut models | 3.3-1 | structured packings | 2.1-1 , 2.1-2 , 2.1-3 , 2.2-1 , 2.2-5 , 6-12 , 6-14 , 6-15 , 6-17 |
| side reactors | 4-7 | surfactant | 5-1 |
| sieve tray | 6-10 | synthesis | 3.1-3 |
| sieve tray column | 3.2-3 | system limit | 2.2-7 |
| sieve tray hydraulics | PL2 | | |
| sieve tray with stabilizer | 6-6 | | |
| silane | 4-1 | | |
| silicon | 4-1 | | |

T

| | | | |
|-------------------------------|-----------------------|----------------------|---------------------|
| thermodynamic analysis | 4-6 | tray columns | 6-6 |
| total reflux operation | 5-2 | trichlorosilane | 4-1 |
| transformed composition space | 6-30 | troubleshooting | PL1 |
| transient flows | 2.2-6 | truncated downcomers | 6-8 |
| tray | 2.2-4 | | |

U

| | | | |
|-------------------------|-----------------------|--------|---|
| ultimate capacity | 2.2-7 | UNIFAC | PL3 , 6-1 |
| ultra-low sulfur diesel | 4-6 | | |

V

| | | | |
|----------------------------|---|-------------------------|---|
| vacuum distillation | 6-26 | vapor-liquid equilibria | 1-3 , 6-1 , 6-2 |
| vapor liquid equilibrium | 1-2 , 6-5 | vapor capacity | 2.2-4 |
| vapor permeation | 4-8 | viscosity | 5-7 |
| vapor pressure correlation | 1-2 | VOF Model | 6-13 |

W

| | | | |
|------------|-----------------------|-------------|----------------------|
| wavy films | 2.2-6 | wetted-wall | 6-12 |
|------------|-----------------------|-------------|----------------------|